#### INDIAN INSTITUTE OF ENGINEERING SCIENCE & TECHNOLOGY

(Formerly Bengal Engineering and Science University, Howrah)

P.O. Botanic Garden, Howrah – 711 103, INDIA.

## (Tel: 91-33-2668 4561 Extn. 600 TENDER NOTICE INVITING QUOTATIONS Ref. No.-Advt. No.- WEB/CST/IIEST/17-18/65 Dated...15-02-2018...

You are invited to submit your most competitive quotation for supply the following items for the CST Department are as follows.

1 Vendors are to collect the original tender document for all items from the Institute Website.

2. Vendors are to submit the tenders in sealed covers super scribing Tender Notice No. on the top of the envelope along with their names and address with phone no. in the office of the CST Department.

3. Vendors are to submit the tender documents in original after accepting the terms and conditions.

4. Last date of submission of tender is 21-02-2018 within 3.00 PM.(on the last date) & offers will be formally opened on the same date at 3.30 PM.

5. The quantity may be changed +/-5% of the quantity as given in the advertisement.

6. Rates quoted inclusive of all taxes.

7.Considering the price of total items order will be placed (as a Trunkey Job)

8. Bills and challans in duplicate should be presented for payment within 15 days of supply & completion of work. All bills are to be accompanied by copy of orders and receipt or challan. order number no. with date , VAT no. and PAN no. are to be mention on both Challan and Bills.

10. Payment will be made by a/c payee cheque or by Account transfer after submission of proper bills and challans. No cash payment will be made under any circumstances. No advance payment can be made.

Signature of the Appropriate authority of the Vendor with Seal

# List of the components:

Sl.No.	Name of the items	Quantity
1	Long Throw Projector	3 Nos.
2.	Short Throw Projector	1 No.

# **Specification**

# 1. <u>LCD Projector Specification</u>

TECHNOLOGY					
Projection System	RGB liquid crystal shutter projection system				
LCD Panel	0.55inch wide panel (D7)				
<b>OPTICAL</b>					
Zoom	1~ 1.3 (Optical)				
Screen Size	30" to 350" [0.88 to 10.44 m] (Zoom: Wide)				
	23" to 260" [0.88 to 10.44 m] (Zoom: Tele)				
<b>Projection Distance</b>	60" screen 1.77 - 2.4 m				
Throw Ratio	1.45 (Zoom: Wide), 1.96 (Zoom: Tele)				
Projection Lens F Number 1.44					
Projection Lens Focal Length 16.7mm					
Focus	Method Manual				
IMAGE					
Colour Light Output	3,200 Lumens				
White Light Output	3,200 Lumens				
Resolution	SVGA				
Native Aspect Ratio	4:3				
Contrast Ratio	15,000:1				
Lamp Hours	5,000 hours (Normal) 10,000 hours (ECO)				
Lamp Type	200 W UHE				
Keystone Correction	Vertical: 30 to +30 degrees Horizontal 30 to +30 degrees				
Tilt Angle	0 to 12 degrees				
<b>CONNECTIVITY</b>					
Input: Video	1 x RCA (Yellow), 1 x S-Video, 1 x Component (via D-sub 15-pin), 1				
x HDMI					
Input: Computer	1 x D-sub 15-Pin (RGB), 1 x USB 2.0 type B				
Input: Digital	1 x HDMI				

Input: Audio 1 x RCA (Red/White), 1 x HDMI Input: Control 1 x USB 2.0 type A Input: Network 1 x USB Type A (for optional Wireless LAN unit) I/O Wireless Connectivity Optional Output Video **Output** Audio Speaker Output 2W**ADVANCED FEATURES** EasyMP Network & Control Yes (with optional Wireless LAN Unit) EasyMP Network Projection Yes (with optional Wireless LAN Unit) PC Free Presentations Yes USB Plug 'n Play Yes AV Mute Slide Yes Instant Off Yes Auto Power On Yes (PC, USB Display) Direct Power On/Off Yes Security Kensington lock Security cable hole Password protect function Colour Modes Dynamic, Presentation, Cinema, sRGB, Blackboard **GENERAL** Dimensions D x W x H (Including Feet) 234 x 297 x 82 mm Weight Approx. 2.4 kg Lamp Warranty 1 Year or 750 hours Projector Warranty 2 Years Power Consumption: Lamp on 277W Power Consumption: Standby 0.26W Noise Level Normal/Eco: 37/28dB

# 2.

#### Short Throw LCD Projector Specification TECHNOLOGY

IEUNULUGI	
Projection System	3LCD Technology
LCD Panel	0.59 inch with MLA (D8)
<b>OPTICAL</b>	
Projection Ratio	0.48:1
Zoom	Digital, Factor: 1 - 1.35
Lens	Optical
Projection Size	53 inches - 116 inches
Projection Distance Wide	0.5 m (53 inch screen)
Projection Distance Tele	1.2 m (116 inch screen)
Projection Lens F Number	1.6
Focal Distance	6.4 mm
Focus	Manual
Offset	9.51 : 1
IMAGE	
Colour Light Output	2,800 Lumen-1,700 Lumen (economy)
White Light Output	2,800 Lumen - 1,700 Lumen (economy) In
	accordance with ISO 21118:2012
Resolution	WXGA, 1280 x 800, 16:10
High Definition	HD ready
Aspect Ratio	16:10
Contrast Ratio	16,000 : 1

Lamp

**Keystone Correction** 

Colour Processing 2D Vertical Refresh Rate Colour Reproduction <u>CONNECTIVITY</u> USB Display Function Interfaces

### **ADVANCED FEATURES**

Security

Features

Interactivity Video Colour Modes

#### GENERAL

Energy Use

Supply Voltage Product dimensions Product weight Noise Level Temperature Humidity Included Software

Options

Loudspeaker What's in the box 200 W, 5,000 h durability, 10,000 h durability (economy mode) Manual vertical: ± 15 °, Manual horizontal ± 15 ° 10 Bits 50 Hz - 85 Hz Upto 1.07 billion colours

3 in 1: Image / Mouse / Sound Cinch audio in, Microphone input, Stereo mini jack audio in (2x), Stereo mini jack audio out, S-Video in, Component in (2x), Composite in, HDMI in, VGA out, VGA in (2x), Wireless LAN IEEE 802.11b/g/n (optional), Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B, USB 2.0 Type A

Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection Built-in speaker, Customizable user logo, Digital zoom, Dynamic lamp control, Horizontal and vertical keystone correction, Long lamp life, Microphone input, Wireless LAN capable No Blackboard, Dynamic, Presentation, sRGB, Theatre

278 Watt, 219 Watt (economy), 0.28 Watt (standby) AC 100 V - 240 V,50 Hz - 60 Hz 345 x 315 x 94 mm (Width x Depth x Height) 3.7 kg Normal: 35 dB (A) - Economy: 29 dB (A) Operation 5° C - 35° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection Connection and control box, Document camera, Ouick wireless USB key, Short throw wall mount, Soft carry case, Wireless LAN unit 16 Watt Computer cable, Main unit, Power cable, Remote control incl. batteries, Setup guide, Software (CD), User manual (CD)