

# INDIAN INSTITUTE OF ENGINEERING SCIENCE AND TECHNOLOGY, SHIBPUR HOWRAH – 711 103, WEST BENGAL

Date: 29/01/2018

### Advt. No. WEB/ARCH/IIESTS/PLAN GRANT/TENDER/2017-18/56

The Department of Architecture, Town and Regional Planning, Indian Institute of Engineering Science and Technology, Shibpur invites sealed quotations from reputed vendors for Supply, Installation and Demonstration of Indoor Air Quality Meter and Data logger. Quotations are to be submitted at the Office of the Head, Department of Architecture, Town and Regional Planning latest by 3.00 PM on 14.02.2018.

Head

Department of Architecture, Town and Regional Planning Indian Institute of Engineering Science and Technology, Shibpur

# INDIAN INSTITUTE OF ENGINEERING SCIENCE AND TECHNOLOGY, SHIBPUR HOWRAH – 711 103, WEST BENGAL

### **NOTICE INVITING TENDER**

Sealed Quotations are invited from reputed vendors on behalf of Department of Architecture, Town and Regional Planning, IIEST, Shibpur for Supply, Installation and Demonstration of Indoor Air Quality Meter and Data logger. Last date for submission of quotation to the office of the Head, Department of Architecture, Town and Regional Planning, Indian Institute of Engineering Science and Technology, Shibpur, is 3.00 PM on February 14, 2018.

LAST DATE AND TIME FOR RECEIVING THE BIDS: 14.2.2018 at 3.00 PM in the Office of the Head, Department of Architecture, Town and Regional Planning, Indian Institute of Engineering Science and Technology, Shibpur.

DATE AND TIME OF OPENING OF BIDS: 14.2.2018 at 4:45 PM at the Office of the Head, Department of Architecture, Town and Regional Planning, Indian Institute of Engineering Science and Technology, Shibpur..

#### REQUIREMENTS AND TECHNICAL SPECIFICATIONS:

## Supply, Installation and Demonstration of Indoor Air Quality Meter and Data logger

Parameters	Specifications			
Type	CO2 Meter with Data Logging capability and Computer			
	interface			
CO <sub>2</sub>	Measuring Principle: Non-dispersive Infrared (NDIR)			
	Technology			
	Sensor Type: Double-beam Infrared Cell Sensor			
	Range: 0 to 5,000 ppm			
	Accuracy: ± 50 ppm ±3% of Value Measured			
	Response Time to 63%: <200 Seconds			
	Resolution: 1 ppm			
Humidity	Type of Sensor: Capacitive			
	Range: 5 to 95% RH			
	Accuracy: ±2% RH			
	Resolution: 0.1% RH			
Temperature	Type of Sensor: CMOS			
	Units: °F or °C			
	Range: -10°C to 60°C (14°F to 140°F)			
	Resolution: 0.1°C/°F			
	Accuracy: ±0.5°C (±0.9°F)			
Sampling Rate	1 Minute to 2 Hours (User Selectable)			
Data Storage Capacity	Up to 1 Million Measurements			
Alarm	Yes			
Display	Dual function LCD			
Backlighting, Display Hold	Yes			
Function				
& Min-Max				
Auto Power-Off	Yes (in Portable Mode Only)			
Operating Range	-10°C to 60°C (14°F to 140°F), 5% to 95% RH			
Circuit	Custom one-chip of Microprocessor LSI circuit			

Power Supply	AA Alkaline Batteries and Rechargeable Battery Connection to			
	230V 60Hz Line/ USB to Wall Adapter			
Communications Interface	Bluetooth Class 2 Wireless Communication/ USB link (the			
	product is then recognized as a USB key for easy file transfer)			
Standards Compliance	IP40 , IEC 61010-1, 50V CAT II - IEC 61326-1			
Mounting	Embedded Magnets on Backside & Tear Drop Wall Hook			
Warranty	03 years on-site warranty (lower warranty period will not be			
	considered for evaluation)			

# **Quantity: 01**

#### **Instructions to Bidders**

## 1. Following to be supplied along with quotation:

- 1. Valid Licence (Trade, etc.) along with Company / Proprietor Pan Card, as applicable.
- 2. Valid GST Registration.
- 3. Documentary proof of Income Tax Return of at least one (1) year from last three (3) financial years.
- 4. Duly signed and self-attested declaration that, the bidder hasn't been blacklisted by any organisation for performing below standard.
- 5. Details of any litigation, current or during the last 3 years in which the bidder is involved, the parties concerned and disputed amount in each case.

#### 2. Bid Price

- a. The contract shall be for the whole works as described in the Requirements and technical specifications as above.
- b. Corrections, if any, shall be made by crossing out, initialing, dating and rewriting.
- c. The bidders are required to quote their rates, both in digits and in words.
- d. All duties, taxes and other levies, payment to persons at delivery counters payable by the bidder under the contract shall be included in the total price.
- e. The rates quoted by the bidder shall be fixed for the duration of the contract and shall not be subject to adjustment on any account.
- f. The rates should be quoted in Indian Rupees only.

## 3. Submission of Quotations

- a. Each bidder shall submit only one quotation.
- b. The quotation submitted by the bidder shall comprise the following along with the documents as specified in Clause No. 1:-
- Quotation in the format given in Annexure 1, duly signed by the bidder;
- ii) Priced Bill of Quantities (BID OFFER) in the format given in Annexure 2, duly signed by the bidder;
- iii) Qualification information as prescribed in Section 1 above duly completed; and
- iv) Bid security @ 2% of the quoted amount in the form of DD/Pay order/Banker's cheque in favour of "Registrar, IIEST, Shibpur" payable at Kolkata, without which quotation will not be considered as a valid bid.

## 4. Bid Security:

- a) The Bid Security shall have to be valid for a period of not less than 80 days after the deadline date specified for submission.
- b) The Bid Security of the unsuccessful bidders will be returned within 28 days of the end of bid validity period specified in Clause No. 8.
- 5. The bidder shall seal the quotation in an envelope addressed to "The Head, Department of Architecture, Town and Regional Planning, Indian Institute of Engineering Science and Technology, Shibpur, Howrah-711103" and mention the Tender Advertisement Number.

The envelope will also bear the following identification: -

#### **Quotation for:**

"Do not open before 16.45 hours February 14, 2018."

- **6.** Quotations must be received in the office of the Head, Department of Architecture, Town and Regional Planning, Indian Institute of Engineering Science & Technology, Shibpur, Howrah-711103, latest within the specified time and date.
- 7. Any quotation received by the office of the Head, Department of Architecture, Town and Regional Planning, Indian Institute of Engineering Science & Technology, Shibpur, Howrah-711103 after the deadline for submission of quotations will be rejected and returned unopened to the bidder.

## 8. Validity of Quotation

Quotation shall remain valid for a period of not less than 45 days after the deadline date specified for submission.

#### 9. Opening of Quotations

Quotations will be opened in the presence of Bidders or their representatives who choose to attend at the specified time and date in the office of "The Head, Department of Architecture, Town and Regional Planning, Indian Institute of Engineering Science & Technology, Shibpur, Howrah-711103."

**10.** Information relating to evaluation of quotations and recommendations for the award of contract shall not be disclosed to bidders or any other persons not officially concerned with the process until the award of contract to the successful bidder is placed.

#### 11. Evaluation of Quotations

The Department of Architecture, Town and Regional Planning authority will evaluate and compare the quotations determined to be substantially responsive i.e. which:

- (a) meet the qualification criteria specified in clause 1 above;
- (b) contain the bid security as specified in clause 3 and 4 above;
- (c) are properly signed; and
- (d) conform to the terms and conditions and specifications without material deviations.

#### 12. Award of contract

The Department of Architecture, Town and Regional Planning authority will award the contract to the bidder whose quotation has been determined to be substantially responsive and who has offered the lowest evaluated quotation price and who meets the specified qualification criteria and provided the bid security.

- **13.** Notwithstanding the above, the The Department of Architecture, Town and Regional Planning authority reserves the right to accept or reject any quotations and to cancel the bidding process and reject all quotations at any time prior to the award of contract.
- **14.** The bidder whose bid is accepted will be notified of the award of contract by the The Department of Architecture, Town and Regional Planning authority prior to expiration of the quotation validity period.

Head

Department of Architecture, Town and Regional Planning Indian Institute of Engineering Science and Technology, Shibpur

# **QUOTATION**

To,

The Head,
Department of Architecture, Town and Regional Planning
Indian Institute of Engineering Science and Technology, Shibpur,
Howrah-711103.
West Bengal.
Subject: Submission of quotation for "Supply, Installation and Demonstration of Indoor Air Quality Meter with Data logger."
Reference: Tender Advt. No. WEB/ARCH/IIESTS/PLAN GRANT/TENDER/2017-18/56 dated January 29, 2018.
Dear Sir/Madam,
I/We offer to execute the works described in tender no. referred above in accordance with the Conditions of Contract enclosed therewith for a total Contract Price of Rs.
[in words]**
This quotation shall constitute a binding contract between us. We understand that you are not bound to accept the lowest or any quotation you receive.
We hereby confirm that this quotation is valid for 45 days as required in Clause 8 of the Instructions to Bidders.
We hereby certify that we have taken steps to ensure that no person acting for us or on our behalf will engage in bribery.
Yours faithfully,
Authorized Signature:
Date:
Name & Title of Signatory:
Contact Address and Phone No. of Bidder:
** To be filled in by the Bidder, together with his particulars and date of submission at the bottom of

<sup>\*\*</sup> To be filled in by the Bidder, together with his particulars and date of submission at the bottom of this form.

**Note:** the Bidder shall attach duly priced and duly signed Bid offer as shown in Annexure-2 of this Tender Document.

# **ANNEXURE-2**

# **BID OFFER**

SI. No.  Description of Items of Work No.  Indoor Air Quality Meter with Data logger  Parameters Type CO. Meter with Data Logging capability and Computer Interface (CO2 Measuring Principle: Non- dispersive Infrared (NIPI) Technology Sensor Type: Double-beam Infrared Cell Sensor Range: 0 to 5,000 ppm Accuracy; ± 50 ppm ± 3% of Value Measured Response Time to 63%: <200 Seconds Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy; ± 29% RH Resolution: 0.1% RH Temperature Type of Sensor: CMOS Units: "F or "C Range: -10"C to 60"C (14"F to 140"F) Resolution: 0.1"C/"F Accuracy; ± 50; (6.0 9"F) Sampling Rate Sampling Rate Sampling Rate Selectable) Data Storage Capacity Alarm Ves Display Dual function LCD Backlighting, Display Poul function LCD Backlighting, Display Poul function LCD Backlighting, Display Dual function LCD Backlighting, Display Poul function LCD Backlighting, Circuit Custom one-chip of Microprocessor LSI circuit Power Supply Rechargeable Battery connection to 230V OPItz Line/ USB to Wall Adapter Communication Bluetooth Cass 2 Wireless Bluetooth Cass 2 Wirel			BID OFFER			_		
Parameters Specifications Type CO2 Meter with Data Logging capability and Computer interface CO2 Measuring Principle: Non-dispersive Infrared (NDIR) Technology Sensor Type: Double-beam Infrared Cell Sensor Range: 0 to 5,000 ppm Accuracy: = 50 ppm = 3% of Value Measured Response Time to 63%: <200 Seconds Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: = 25% RH Resolution: 0.1% RH Temperature Units: "F or "C Range: -10"C to 60"C (14"F to 140"F) Resolution: 0.1"C/"F Accuracy: = 20.5"C (=0.9"F)  Sampling Rate Infinite to 2 Hours (User Selectable) Data Storage Up to 1 Million Measurements Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function R Min-Max Auto Power- Off Custom one-chip of Min-Power Supply Resolage Battery Connection Crown United Batteries and Recharged Re	No.	Description of Items of Work			GST	unit including	·	
Type CO2 Meter with Data Logging capability and Computer interface  CO2 Measuring Principle: Non- dispersive Infrared (NDIR) Technology Sensor Type: Double-beam Infrared Cell Sensor Range: 0 to 5,000 ppm Accuracy: ± 50 ppm +3% of Value Measured Response Time to 63%: <200 Seconds Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH Temperature Type of Sensor: CMOS Units: *F or *C' Range: -10** C to 60** C (14*F to 140*F) Resolution: 0.1** C/F Accuracy: -3.5** C (4.9*F)  Sampling Rate 1 Minute to 2 Hours (User Selectable) Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating -10** C to 60** C (14*F to 140*F), 5% to 95% RH Circuit Custom one-chip of Microprocessor LSI circuit Power Supply AA Alkaline Batteries and Recharged and Recharged Recharge	1	Indoor Air Qua	ality Meter with Data logger				01	
Type CO2 Meter with Data Logging capability and Computer interface  CO2 Measuring Principle: Non- dispersive Infrared (NDIR) Technology Sensor Type: Double-beam Infrared Cell Sensor Range: 0 to 5,000 ppm Accuracy: ± 50 ppm +3% of Value Measured Response Time to 63%: <200 Seconds Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH Temperature Type of Sensor: CMOS Units: *F or *C' Range: -10** C to 60** C (14*F to 140*F) Resolution: 0.1** C/F Accuracy: -3.5** C (4.9*F)  Sampling Rate 1 Minute to 2 Hours (User Selectable) Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating -10** C to 60** C (14*F to 140*F), 5% to 95% RH Circuit Custom one-chip of Microprocessor LSI circuit Power Supply AA Alkaline Batteries and Recharged and Recharged Recharge		Davamatana	Considerations					
capability and Computer interface  CO2  Measuring Principle: Non-dispersive Infrared (NDIR) Tachnology Sensor Type: Double-beam Infrared Cell Sensor Range: 0 to 5,000 ppm Accuracy: ±50 ppm ±3% of Value Measured Response Time to 63%: <200 Seconds Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH Temperature Type of Sensor: CMOS Units: *F or *C Range: -10** C to 60** C (14*F to 140*F) Resolution: 0.1** C/F Accuracy: ±0.5** C (±0.9*F)  Sampling Rate Thim to 2 Hours (User Selectable) Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function Re Min-Max Auto Power- Off Operating Alaine Batteries and Rechargesable Battery Connection to 230** 60** Electable) Custom one-Chip of Microprocessor LSI circuit Power Supply Alaine Batteries and Rechargesable Battery Connection to 230** 60** Electable) Alaine Batteries and Rechargesable Battery Connection to 230** 60** Class 2 Wireless			. •					
CO2  Measuring Principle: Non- dispersive Infrared (NDIR) Technology Sensor Type: Double-beam Infrared Cell Sensor Range: 0 to 5,000 ppm Accuracy: ± 50 ppm ±3% of Value Measured Response Time to 63%: <200 Seconds Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH Temperature Type of Sensor: CMOS Units: "F or "C Range: -10°C to 60°C (14"F to 140"F) Resolution: 0.1"C/"F Accuracy: ±0.5"C (±0.9"F)  Sampling Rate Ti Minute to 2 Hours (User Selectable) Data Storage Up to 1 Million Measurements Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating Analy Alarine Mode Only) Off Operating Circuit Custom one-chip of Microprocessor LSI circuit Power Supply A Alaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless		туре						
dispersive Infrared (NDIR) Technology Sensor Type: Double-beam Infrared Cell Sensor Range: 0 to 5,000 ppm Accuracy: ±50 ppm ±3% of Value Measured Response Time to 63%: <200 Seconds Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH Temperature Type of Sensor: CMOS Units: *For *C' Range: -10**C to 60**C (14*F to 140*F) Resolution: 0.1**C/F Accuracy: ±0.5**C (±0.9*F)  Sampling Rate I Minute to 2 Hours (User Selectable) Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating Range 1-0**C (14*F to 140*F), 5% to 95% RH Circuit Custom one-chip of Microprocessor LSI circuit Power Supply A A Alkaline Batteries and Rechargeable Battery Connection to 230** 60**LEINE Usel to Wall Adapter Communication Bluetooth Class 2 Wireless		COs	1 1 3 1	1				
Technology Sensor Type: Double-beam Infrared Cell Sensor Range: 0 to 5,000 ppm Accuracy: ± 50 ppm ±3% of Value Measured Response Time to 63%: <200 Seconds Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH Temperature Type of Sensor: CMOS Units: "F or "C Range: 10"C to 60"C (14"F to 140"F) Resolution: 0.1"C/"F Accuracy: ±0.5"C (±0.9"F)  Sampling Rate 1 Minute to 2 Hours (User Selectable) Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating -10"C to 60"C (14"F to 140"F), 5% Range Circuit Custom one-chip of Microprocessor LSI circuit Power Supply AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless		002						
Sensor Type: Double-beam Infrared Cell Sensor Range: 0 to 5,000 ppm Accuracy: ± 50 ppm ±3% of Value Measured Response Time to 63%: <200 Seconds Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH Temperature Type of Sensor: CMOS Units: "F or "C Range: -10"C to 60"C (14"F to 140"F) Resolution: 0.1"C/"F Accuracy: ±0.5"C (±0.9"F)  Sampling Rate I Minute to 2 Hours (User Selectable) Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Ves (in Portable Mode Only) Off Operating -10"C to 60"C (14"F to 140"F), 5% Range to 95% RH Circuit Custom one-chip of Microprocessor LSI circuit Power Supply Adapter Communicatio Bluetooth Class 2 Wireless								
Range: 0 to 5,000 ppm Accuracy: ± 50 ppm ±3% of Value Measured Response Time to 63%: <200 Seconds Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH Temperature Type of Sensor: CMOS Units: "for "C Range: -10"C to 60"C (14"F to 140"F) Resolution: 0.1"C/"F Accuracy: ±0.5"C (±0.9"F)  Sampling Rate 1 Minute to 2 Hours (User Selectable) Data Storage Capacity Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating -10"C to 60"C (14"F to 140"F), 5% Range to 95% RH Circuit Custom one-chip of Microprocessor LSI circuit Power Supply Adapter Communicatio Bluetooth Class 2 Wireless								
Accuracy: ± 50 ppm ±3% of Value Measured Response Time to 63%: <200 Seconds Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH Temperature Type of Sensor: CMOS Units: "F or "C Range: -10"C to 60"C (14"F to 140"F) Resolution: 0.1"c/"F Accuracy: ±0.5"C (±0.9"F)  Sampling Rate 1 Minute to 2 Hours (User Selectable) Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating Anne -10"C to 60"C (14"F to 140"F), 5% to 98 RH Circuit Custom one-chip of Microprocessor LSI circuit Power Supply Alater Communicatio Bluetooth Class 2 Wireless			Infrared Cell Sensor					
Messured Response Time to 63%: <200 Seconds Resolution: 1 ppm  Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH  Temperature Type of Sensor: CMOS Units: "F or "C Range: -10"C to 60"C (14"F to 140"F) Resolution: 0.1"C/"F Accuracy: ±0.5"C (±0.9"F)  Sampling Rate I Minute to 2 Hours (User Selectable) Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, DisplayHold Function & Min-Max Auto Power- Operating Range To 95% RH Circuit Custom one-chip of Microprocessor LSI circuit Power Supply A Al Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless								
Response Time to 63%: <200 Seconds Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH Temperature Type of Sensor: CMOS Units: "F or "C Range: -10°C to 60°C (14°F to 140°F) Resolution: 0.1°C/F Accuracy: ±0.5°C (±0.9°F)  Sampling Rate 1 Minute to 2 Hours (User Selectable) Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating Anney 1-10°C to 60°C (14°F to 140°F), 5% to 10°C (14°F to 140°F), 5% Range to 95% RH Circuit Custom one-chip of Microprocessor LSI circuit Power Supply A AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless								
Seconds Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH  Temperature Type of Sensor: CMOS Units: "F or "C Range: -10"C to 60"C (14"F to 140"F) Resolution: 0.1"C/"F Accuracy: ±0.5"C (±0.9"F)  Sampling Rate 1 Minute to 2 Hours (User Selectable) Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating -10"C to 60"C (14"F to 140"F), 5% to 95% RH Circuit Custom one-chip of Microprocessor LSI circuit Power Supply AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless								
Resolution: 1 ppm Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH Temperature Type of Sensor: CMOS Units: "F or "C Range: -10°C to 60°C (14°F to 140°F) Resolution: 0.1°C/"F Accuracy: ±0.5°C (±0.9°F)  Sampling Rate 1 Minute to 2 Hours (User Selectable) Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating -10°C to 60°C (14°F to 140°F), 5% Range to 95% RH Circuit Custom one-chip of Microprocessor LSI circuit Power Supply Aklaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless								
Humidity Type of Sensor: Capacitive Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH Temperature Type of Sensor: CMOS Units: "F or "C Range: -10°C to 60°C (14°F to 140°F) Resolution: 0.1°C/"F Accuracy: ±0.5°C (±0.9°F)  Sampling Rate 1 Minute to 2 Hours (User Selectable) Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, DisplayHold Function & Min-Max Auto Power- Off Operating -10°C to 60°C (14°F to 140°F), 5% Range to 95% RH Circuit Custom one-chip of Microprocessor LSI circuit Power Supply AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless								
Range: 5 to 95% RH Accuracy: ±2% RH Resolution: 0.1% RH  Temperature Type of Sensor: CMOS Units: "F or "C Range: -10"C to 60"C (14"F to 140"F) Resolution: 0.1"C/"F Accuracy: ±0.5"C (±0.9"F)  Sampling Rate T Minute to 2 Hours (User Selectable) Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating Operating Circuit Custom one-chip of Microprocessor LSt circuit Power Supply AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless		Humidity		-				
Accuracy: ±2% RH Resolution: 0.1% RH  Temperature  Type of Sensor: CMOS Units: "F or "C Range: -10"C to 60"C (14"F to 140"F) Resolution: 0.1"C/"F Accuracy: ±0.5"C (±0.9"F)  Sampling Rate  1 Minute to 2 Hours (User Selectable)  Data Storage Capacity Alarm Yes Display Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating Aune Circuit Cruit Custom one-chip of Microprocessor LSI circuit Power Supply AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless		liamary						
Temperature  Type of Sensor: CMOS Units: "F or "C Range: -10°C to 60°C (14°F to 140°F) Resolution: 0.1°C/°F Accuracy: ±0.5°C (±0.9°F)  Sampling Rate  I Minute to 2 Hours (User Selectable)  Data Storage Capacity Alarm Yes Display Dual function LCD Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating Circuit Custom one-chip of Microprocessor LSI circuit Power Supply  AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter  Communicatio  Bluetooth Class 2 Wireless								
Units: "F or "C Range: -10"C to 60"C (14"F to 140"F) Resolution: 0.1"C/"F Accuracy: ±0.5"C (±0.9"F)  Sampling Rate  1 Minute to 2 Hours (User Selectable)  Data Storage Capacity  Alarm Yes Display Dual function LCD  Backlighting, Display Hold Function & Min-Max Auto Power- Off Operating Range to 95% RH Circuit  Custom one-chip of Microprocessor LSI circuit  Power Supply  AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter  Communicatio  Biuetooth Class 2 Wireless			1					
Range: -10°C to 60°C (14°F to 140°F) Resolution: 0.1°C/F Accuracy: ±0.5°C (±0.9°F)  Sampling Rate  1 Minute to 2 Hours (User Selectable)  Data Storage Capacity  Alarm Yes Display Dual function LCD Backlighting, Display Hold Function & Min-Max  Auto Power- Off Operating -10°C to 60°C (14°F to 140°F), 5% Range to 95% RH Circuit Custom one-chip of Microprocessor LSI circuit  Power Supply AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless		Temperature						
140°F)   Resolution: 0.1°C/°F   Accuracy: ±0.5°C (±0.9°F)     Sampling Rate								
Accuracy: ±0.5°C (±0.9°F)  Sampling Rate 1 Minute to 2 Hours (User Selectable)  Data Storage Capacity  Alarm Yes  Display Dual function LCD  Backlighting, Ves  Display Hold Function & Win-Max  Auto Power-Off  Operating -10°C to 60°C (14°F to 140°F), 5% to 95% RH  Circuit Custom one-chip of Microprocessor LSI circuit  Power Supply AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter  Communicatio Bluetooth Class 2 Wireless			140°F)					
Sampling Rate 1 Minute to 2 Hours (User Selectable)  Data Storage Capacity Up to 1 Million Measurements  Alarm Yes Display Dual function LCD  Backlighting, Display Hold Function & Min-Max  Auto Power-Off Operating -10°C to 60°C (14°F to 140°F), 5% Range to 95% RH  Circuit Custom one-chip of Microprocessor LSI circuit  Power Supply AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter  Communicatio Bluetooth Class 2 Wireless								
Selectable)  Data Storage Capacity  Alarm  Yes  Display  Dual function LCD  Backlighting, Ves  Display Hold  Function  & Min-Max  Auto Power-Off  Operating  Circuit  Custom one-chip of  Microprocessor LSI circuit  Power Supply  AA Alkaline Batteries and  Rechargeable Battery Connection  to 230V 60Hz Line/ USB to Wall  Adapter  Communicatio  Bluetooth Class 2 Wireless				-				
Capacity  Alarm  Alarm  Yes  Display  Dual function LCD  Backlighting, Display Hold Function  & Min-Max  Auto Power- Off  Operating Ange  to 95% RH  Circuit  Custom one-chip of Microprocessor LSI circuit  Power Supply  AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter  Communicatio  Bluetooth Class 2 Wireless		Sampling Rate						
Display  Backlighting, Display Hold Function & Min-Max  Auto Power- Off  Operating Range to 95% RH  Circuit  Custom one-chip of Microprocessor LSI circuit  Power Supply  AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter  Communicatio  Bluetooth Class 2 Wireless			Up to 1 Million Measurements					
Backlighting, Display Hold Function & Min-Max  Auto Power- Off  Operating Range  to 95% RH  Circuit  Custom one-chip of Microprocessor LSI circuit  Power Supply  AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter  Communicatio  Bluetooth Class 2 Wireless								
Display Hold Function & Min-Max  Auto Power- Off  Operating Range to 95% RH  Circuit Custom one-chip of Microprocessor LSI circuit  Power Supply  AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter  Communicatio  Bluetooth Class 2 Wireless								
Function & Min-Max  Auto Power- Off  Operating Range to 95% RH  Circuit Custom one-chip of Microprocessor LSI circuit  Power Supply AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter  Communicatio Bluetooth Class 2 Wireless		0 0	Yes					
& Min-Max Auto Power- Off Operating -10°C to 60°C (14°F to 140°F), 5% Range to 95% RH Circuit Custom one-chip of Microprocessor LSI circuit Power Supply AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless								
Auto Power- Off Operating -10°C to 60°C (14°F to 140°F), 5% Range to 95% RH Circuit Custom one-chip of Microprocessor LSI circuit Power Supply AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless								
Range to 95% RH  Circuit Custom one-chip of Microprocessor LSI circuit  Power Supply AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter  Communicatio Bluetooth Class 2 Wireless		Auto Power-	Yes (in Portable Mode Only)					
Range to 95% RH  Circuit Custom one-chip of Microprocessor LSI circuit  Power Supply AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter  Communicatio Bluetooth Class 2 Wireless			-10°C to 60°C (14°F to 140°F), 5%	1				
Microprocessor LSI circuit  Power Supply  AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter  Communicatio  Bluetooth Class 2 Wireless			to 95% RH					
Power Supply  AA Alkaline Batteries and Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter  Communicatio Bluetooth Class 2 Wireless		Circuit						
Rechargeable Battery Connection to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless		Davis Co. 1						
to 230V 60Hz Line/ USB to Wall Adapter Communicatio Bluetooth Class 2 Wireless		Power Supply						
Adapter Communicatio Bluetooth Class 2 Wireless								
Communicatio Bluetooth Class 2 Wireless								
		Communicatio		1				

SI. No.	Description of Items of Work		Unit Rate	GST	Total price per unit including GST	Ωty	Gross Amount (Rs.)
		product is then recognized as a					
	Standards Compliance	USB key for easy file transfer) IP40 , IEC 61010-1, 50V CAT II - IEC 61326-1					
	Mounting	Embedded Magnets on Backside & Tear Drop Wall Hook					
	Warranty	03 years on-site warranty (lower warranty period will not be considered for evaluation)					
	Demonstration /Training	In site demonstration/training at the convenience of the buyer.					
	Total amount for the supply, installation and demonstration of the equipment inclusive of 03 years on-site warranty.						

Authorized Signature:	
Date:	
Name & Title of Signatory:	
Contact Address and Phone No. of Bidder:	